



Rainier [CL] Dim to Warm

SURFACE / SUSPENSION / WALL MOUNT



24V
DC

DRY
RATED

DAMP
RATED


WET
RATED

For use with Light Source.

SPECIFICATIONS

Output Options	100lm/ft		300lm/ft
Watts per Foot (White Lens)	4.0W		7.4W
Max Run Length (White Lens)	27ft		14ft
Light Color (CCT)	1800K – 3000K	1800K – 3500K	1800K – 4000K
Color Rendering	95+ CRI / 2-Step		
Lenses	White Flush Lens, White Lens + Linear Louver, White Lens + Hex Louver		
Mounting	Mounting Clip, Suspension Kit, Wall Mount Kit		
Finish	Black		
Input Voltage	24VDC (Power Supply: 120VAC – 277VAC)		
Dimming	TRIAC, ELV, 0-10V, DMX, DALI, Bluetooth		
Dimensions	12.00" (304.8mm) × 0.79" (20.0mm) × 0.66" (16.7mm)		
Production Interval	2.81" (71.4mm)		
Operating Temperature	-4°F (-20°C) to 113°F (45°C)		

FIXTURE DIMENSIONS




Side View



Top View with Linear Louver



Top View with Hex Louver



PROJECT NAME _____ FIXTURE TYPE _____ LOCATION _____



Rainier [CL] Dim to Warm

SURFACE / SUSPENSION / WALL MOUNT



WHITE LENS DELIVERED LM/FT

	3000K	3500K	4000K
100lm/ft	188	190	198
300lm/ft	347	365	367

PROJECT NAME _____

FIXTURE TYPE _____

LOCATION _____




Rainier [CL] Dim to Warm

SURFACE / SUSPENSION / WALL MOUNT




ACCESSORIES DIMENSIONS


Mounting Clip



Suspension



Linear & Hex Louver



RAINIER [CL] DIM TO WARM COMPONENTS

Rainier [CL] - Profile



[Click here to view the Spec Sheet →](#)

Dim to Warm LED Tape - High Density



[Click here to view the Spec Sheet →](#)

PROJECT NAME _____

FIXTURE TYPE _____

LOCATION _____



Rainier [CL] Dim to Warm

SURFACE / SUSPENSION / WALL MOUNT



PART NUMBER EXAMPLE

ILL-RA06-DW - I - 1830K - 100 - WH - MC - BK - 50" - E2 - C
+
PS - UNIV - 24V - 100W - JBOX

PART NUMBER BUILDER

SERIES	DRY/WET	CCT	OUTPUT	LENS	MOUNTING	FINISH
ILL-RA06-DW -	-	-	-	-	-	BK
iLuminate Rainier [CL] Dim to Warm	I - Indoor O - Outdoor	1830K - 1800K - 3000K 1835K - 1800K - 3500K 1840K - 1800K - 4000K	100 - 100lm/ft 300 - 300lm/ft	WH - White Lens WL - White Lens + Linear Louver WX - White Lens + Hex Louver	MC - Mounting Clips SP - Suspension Kit WL - Wall Mount Kit	BK - Black
LENGTH (IN)		START FEED		END FEED		
		TYPE	LENGTH	TYPE	LENGTH	
Fixtures will be built as close to the requested length without going over based on 2.81" (71.4mm) production interval. Lengths longer than 78in will consist of multiple pieces of channel and lens to be assembled in the field to create the complete fixture length.		E - End	Blank - Endcap	E - End	Blank - Endcap	
		B - Back	2 - 2ft 5 - 5ft 10 - 10ft 15 - 15ft 20 - 20ft 25 - 25ft	B - Back C - Endcap	2 - 2ft 5 - 5ft 10 - 10ft 15 - 15ft 20 - 20ft 25 - 25ft	

POWER SUPPLY

SERIES	CONTROL	VOLTAGE OUTPUT	MAX WATTAGE OUTPUT	FORM
PS	-	24V	-	-
iLuminate AC to DC Constant Voltage Power Supply	UNIV - Universal 5-in-1 DMX - DMX512 Enabled DALI - DALI-2 Enabled BLE - Bluetooth Enabled	24V - 24VDC	30W - 30W 60W - 60W 100W - 100W 200W - 100W x 2 300W - 100W x 3	JBOX - Dry/Damp Rated IP66 - Wet Rated

PROJECT NAME _____ FIXTURE TYPE _____ LOCATION _____