



Rainier [CL] Tunable White

SURFACE / SUSPENSION / WALL MOUNT




For use with Light Source.

SPECIFICATIONS

Output Options	100lm/ft
Watts per Foot (White Lens)	4.4W (All On)
Max Run Length (White Lens)	16.4ft
Light Color (CCT)	1800K - 3000K 1800K - 3500K 1800K - 4000K
Color Rendering	95+ CRI / 3-Step
Lenses	White Flush Lens, White Lens + Linear Louver, White Lens + Hex Louver
Mounting	Mounting Clip, Suspension Kit, Wall Mount Kit
Finish	Black
Input Voltage	24VDC (Power Supply: 120VAC - 277VAC)
Dimming	PWM, DMX, DALI, Bluetooth
Dimensions	12.00" (304.8mm) × 0.79" (20.0mm) × 0.66" (16.7mm)
Production Interval	1.31" (33.3mm)
Operating Temperature	-4°F (-20°C) to 113°F (45°C)

FIXTURE DIMENSIONS




Side View



Top View with Linear Louver



Top View with Hex Louver



PROJECT NAME _____ FIXTURE TYPE _____ LOCATION _____



Rainier [CL] Tunable White

SURFACE / SUSPENSION / WALL MOUNT



WHITE LENS DELIVERED LM/FT				
	1800K	3000K	3500K	4000K
100lm/ft	116	160	163	166

PROJECT NAME _____ FIXTURE TYPE _____ LOCATION _____




Rainier [CL] Tunable White

SURFACE / SUSPENSION / WALL MOUNT




ACCESSORIES DIMENSIONS


Mounting Clip



Suspension



Linear & Hex Louver



RAINIER [CL] TUNABLE WHITE COMPONENTS

Rainier [CL] - Profile



[Click here to view the Spec Sheet →](#)

Tunable White LED Tape - High Density



[Click here to view the Spec Sheet →](#)

PROJECT NAME _____ FIXTURE TYPE _____ LOCATION _____



Rainier [CL] Tunable White

SURFACE / SUSPENSION / WALL MOUNT



PART NUMBER EXAMPLE

ILL-RA06-TW - I - 1830K - 100 - WH - MC - BK - 50" - E2 - C
+
PS - UNIV - 24V - 100W - JBOX

PART NUMBER BUILDER

SERIES	DRY/WET	CCT	OUTPUT	LENS	MOUNTING	FINISH
ILL-RA06-TW -	-	-	100	-	-	BK
iLuminate Rainier [CL] Tunable White	I - Indoor	1830K - 1800K - 3000K	100 - 100lm/ft	WH - White Lens	MC - Mounting Clip	BK - Black
	O - Outdoor	1835K - 1800K - 3500K		WL - White Lens + Linear Louver	SP - Suspension Kit	
		1840K - 1800K - 4000K		WX - White Lens + Hex Louver	WL - Wall Mount Kit	
LENGTH (IN)		START FEED		END FEED		
		TYPE	LENGTH	TYPE	LENGTH	
<i>Fixtures will be built as close to the requested length without going over based on 1.31" (33.3mm) production interval.</i>		E - End	Blank - Endcap	E - End	Blank - Endcap	
		B - Back	2 - 2ft	B - Back	2 - 2ft	
<i>Lengths longer than 78in will consist of multiple pieces of channel and lens to be assembled in the field to create the complete fixture length.</i>			5 - 5ft	C - Endcap	5 - 5ft	
			10 - 10ft		10 - 10ft	
			15 - 15ft		15 - 15ft	
			20 - 20ft		20 - 20ft	
			25 - 25ft		25 - 25ft	

POWER SUPPLY

SERIES	CONTROL	VOLTAGE OUTPUT	MAX WATTAGE OUTPUT	FORM
PS	-	24V	-	
iLuminate AC to DC Constant Voltage Power Supply	UNIV - Universal 5-in-1	24V - 24VDC	30W - 30W	JBOX - Dry/Damp Rated
	DMX - DMX512 Enabled		60W - 60W	IP66 - Wet Rated
	DALI - DALI-2 Enabled		100W - 100W	
	BLE - Bluetooth Enabled		200W - 100W x 2	
			300W - 100W x 3	

PROJECT NAME _____ FIXTURE TYPE _____ LOCATION _____