

Rainier [SF] Full Spectrum

SURFACE / SUSPENDED

ilLumenate
lighting

24V
DC

DRY
RATED

DAMP
RATED


WET
RATED

For use with  Light Source.

SPECIFICATIONS

Output Options	100lm/ft
Watts per Foot (White Lens)	8W (All On)
Max Run Length (White Lens)	16.4ft
Light Color (CCT)	RGB + 1800K + 4000K
Color Rendering	W = 90+ CRI / 3-Step
Lenses	White Flush Lens, White Lens + Linear Louver, White Lens + Hex Louver
Mounting	Clip, Magnet, Suspension
Finish	Black
Input Voltage	24VDC (Power Supply: 120VAC - 277VAC)
Dimming	PWM, DMX, DALI, Bluetooth
Dimensions	12.00" (304.8mm) x 0.59" (15mm) x 0.59" (15mm)
Production Interval	4.00" (101.6mm)
Operating Temperature	-4°F (-20°C) to 113°F (45°C)


Fixture Dimensions



Side View



Top View with Linear Louver




Top View with Hex Louver

PROJECT NAME _____

Fixture Type _____

LOCATION _____



Rainier [SF] Full Spectrum

SURFACE / SUSPENSION

ilLumenate
lighting

WHITE LENS DELIVERED LM/FT

	Red	Green	Blue	1800K	4000K
100 Output	34	48	23	120	120

PROJECT NAME _____

Fixture Type _____

LOCATION _____




Rainier [SF] Full Spectrum

SURFACE / SUSPENSION


ilLumenate
lighting

ACCESSORIES DIMENSIONS


Mounting Clip




Magnet Mounting



Suspension



Linear & Hex Louver



RAINIER [SF] FULL SPECTRUM COMPONENTS

Rainier [SF] - Profile



[Click here to view the Spec Sheet →](#)

Full Spectrum LED Tape



[Click here to view the Spec Sheet →](#)

PROJECT NAME _____

Fixture Type _____

LOCATION _____



Rainier [SF] Full Spectrum

SURFACE / SUSPENSION



PART NUMBER EXAMPLE

ILL-RA01-FS - I - RGB1840K - 100 - WH - MC - BK - 50" - E2 - C
+
PS - UNIV - 24V - 100W - JBOX

PART NUMBER BUILDER

SERIES	DRY/WET	CCT	OUTPUT	LENS	MOUNTING	FINISH
ILL-RA01-FS -	I	RGB1840K	100			BK
iLumenate Rainier [SF] Full Spectrum	I - Indoor	RGB1840K	100 - 100lm/ft	WH - White Lens WL - White Lens + Linear Louver WX - White Lens + Hex Louver	MC - Mounting Clip MG - Magnet SP - Suspension	BK - Black

LENGTH (IN)	START FEED TYPE	LENGTH	END FEED TYPE	LENGTH
Fixtures will be built as close to the requested length without going over based on 4.00" (101.6mm) production interval.				
Lengths longer than 78in will consist of multiple pieces of channel and lens to be assembled in the field to create the complete fixture length.	E - End	Blank - Endcap	E - End	Blank - Endcap
	B - Back	2 - 2ft	B - Back	2 - 2ft
		5 - 5ft	C - Endcap	5 - 5ft
		10 - 10ft		10 - 10ft
		15 - 15ft		15 - 15ft
		20 - 20ft		20 - 20ft
		25 - 25ft		25 - 25ft

POWER SUPPLY

SERIES	CONTROL	VOLTAGE OUTPUT	MAX WATTAGE OUTPUT	FORM
PS -		24V -		
iLumenate AC to DC Constant Voltage Power Supply	UNIV - Universal 5-in-1 DMX - DMX512 Enabled DALI - DALI-2 Enabled BLE - Bluetooth Enabled	24V - 24VDC	30W - 30W 60W - 60W 100W - 100W 200W - 100W x 2 300W - 100W x 3	JBOX - Dry/Damp Rated IP66 - Wet Rated

PROJECT NAME _____

Fixture Type _____

LOCATION _____